

## UNIT SPECIFICATION DATA SHEET

UNIT MODEL  
HPHWW100 SS

Water To Water Heat Pump

### FEATURE INFORMATION

CABINET	Stainless Steel
COND. COIL	Coaxial - Cupronickel
COND FANS	N/A
EVAP. COIL	Coaxial Tube in Tube Cupronickel
REF. CIRCUITS	Independent Circuit
SAFETY	High/Low Press. Switches, Overload Protection, Anti-Freeze Protection, Time Delay, Lock-out Relay, Phase Monitor and Voltage Protection
& CONTROL	24 Volt, Digital Control

### UNIT PERFORMANCE

TOTAL COOLING CAPACITY- BTU/HR	98000
HEATING CAPACITY	123000
WATER PRESSURE DROP FT H <sub>2</sub> O	20.1
EVAPORATOR WATER FLOW - GPM	19
EVAPORATOR ENTERING WATER TEMP. °F	55.0
EVAPORATOR LEAVING WATER TEMP. °F	45
CONDENSER WATER FLOW - GPM	25
CONDENSER ENTERING WATER TEMP. °F	86
E.E.R.	13.3
C.O.P (HEAT-PUMP ONLY)	4.3
MIN AMP. / MAX FUSE - AMPS.	34 / 60
VOLTAGE RATING / PHASE / HERTZ	208-230/1/60
DIMENSION W" X L" X H"	40.25 x 31 x 25
WEIGHT - NET	410



1. UNIT IS SUBJECT TO CHANGE WITHOUT NOTICE
2. UNIT IF AVAILABLE IN DIFFERENT CONFIGURATIONS AND VOLTAGE RATINGS