

UNIT SPECIFICATION DATA SHEET

UNIT MODEL
HPHWW120 SS

Water To Water Heat Pump

FEATURE INFORMATION

CABINET	Stainless Steel
COND. COIL	Coaxial - Cupronickel
COND FANS	N/A
EVAP. COIL	Coaxial Tube in Tube Cupronickel
REF. CIRCUITS	2 Independent Circuit
SAFETY	High/Low Press. Switches, Overload Protection, Anti-Freeze Protection, Time Delay, Lock-out Relay, Phase Monitor and Voltage Protection
& CONTROL	24 Volt, Digital Control

UNIT PERFORMANCE

TOTAL COOLING CAPACITY- BTU/HR	115700
HEATING CAPACITY	147500
WATER PRESSURE DROP FT H2O	21
EVAPORATOR WATER FLOW - GPM	24
EVAPORATOR ENTERING WATER TEMP. °F	55.0
EVAPORATOR LEAVING WATER TEMP. °F	45.2
CONDENSER WATER FLOW - GPM	30
CONDENSER ENTERING WATER TEMP. °F	85
E.E.R.	13.1
C.O.P (HEAT-PUMP ONLY)	4.4
MIN AMP. / MAX FUSE - AMPS.	38.6 / 50
VOLTAGE RATING / PHASE / HERTZ	208-230/3/60
DIMENSION W" X L" X H"	40.25 x 31 x 26
WEIGHT - NET	456



1. UNIT IS SUBJECT TO CHANGE WITHOUT NOTICE
2. UNIT IF AVAILABLE IN DIFFERENT CONFIGURATIONS AND VOLTAGE RATINGS