

UNIT SPECIFICATION DATA SHEET

UNIT MODEL
HPHWW060 SS

Water To Water Heat Pump

FEATURE INFORMATION

CABINET	Stainless Steel
COND. COIL	Coaxial - Cupronickel
COND FANS	N/A
EVAP. COIL	Coaxial Tube in Tube Cupronickel
REF. CIRCUITS	1 Independent Circuit
SAFETY	High/Low Press. Switches, Overload Protection, Anti-Freeze Protection, Time Delay, Lock-out Relay, Phase Monitor and Voltage Protection
& CONTROL	24 Volt, Digital Control

UNIT PERFORMANCE

TOTAL COOLING CAPACITY- BTU/HR	58200
HEATING CAPACITY	68800
WATER PRESSURE DROP FT H2O	18.6
EVAPORATOR WATER FLOW - GPM	9.6
EVAPORATOR ENTERING WATER TEMP. °F	55.0
EVAPORATOR LEAVING WATER TEMP. °F	45
CONDENSER WATER FLOW - GPM	15
CONDENSER ENTERING WATER TEMP. °F	85
E.E.R.	13.1
C.O.P (HEAT-PUMP ONLY)	4.4
MIN AMP. / MAX FUSE - AMPS.	38.6 / 50
VOLTAGE RATING / PHASE / HERTZ	208-230/1/60
DIMENSION W" X L" X H"	21.5 x 33 x 20.75
WEIGHT - NET	300

1. UNIT IS SUBJECT TO CHANGE WITHOUT NOTICE
2. UNIT IF AVAILABLE IN DIFFERENT CONFIGURATIONS AND VOLTAGE RATINGS